

Tel: 07 3897 5700 Fax: 07 3283 1168 ecb@ecb.com.au www.ecb.com.au 29 Snook St Clontarf QLD 4019 Australia

Po Box 122 Margate QLD 4019 Australia

BSZ58SY

REPLACES: 16.03.10 REVISED: 17.01.18

FITTING INSTRUCTIONS

GRAND VITARA 08/05-07/08 BIG TUBE™ WITH FOG LIGHTS VEHICLE FRONTAL PROTECTION SYSTEM (VFPS) FOR AIR BAG & ADR COMPLIANT VEHICLES

Check installation hardware before commencing. Required tools: Long 10mm drill bits for mild steel

- 1. Lift bonnet.
- 2. Remove grille. Four plastic push in/out clips at top, lift upwards and slightly outwards to release off lower clips.
- 3. Remove bumper cover by the following: Remove two 10mm head screws (from behind grille). Remove four plastic push in/out clips from top of bumper cover / grille area. Remove two plastic push in/out clips (each side) from plastic inner guard. Remove one PK self-tapper screw (each side) from top of bumper cover side return. From along bottom of bumper cover remove three PK self-tappers, two 10mm head screws and six plastic push in/out clips.

Pull outwards at side returns to release off clips. **See figure 1.** Pull forward off vehicle. **NOTE**: Unplug temp sensor wiring as removing.

- 4. Die grind one side of large chassis hole to allow two bolts and washers on wire to fit through. See figure 2. Blow all filings clear and treat all exposed metal with a rust inhibitor.
- 5. For turbo diesel vehicles: Remove M6 bolt on front of chassis rail, attaching lower mount of intercooler. When sliding ECB steel mount down in Step 6, ensure mount sits behind intercooler mount.
- 6. Place steel mounting brackets (supplied) in from top of chassis and push down until 8mm hole in ECB steel mount aligns with captive nut on front of chassis. Attach using M6 bolt, spring washers and flat washers (supplied). **FINGER TIGHTEN ONLY. See figure 3.**
- 7. Align side mount plates to front of chassis rail. Using ECB steel mount as a guide, drill holes into outside of chassis rail with long 10mm drill bit. See figure 4. Treat all exposed metal with a rust inhibitor.
- 8. Bend wire to shape and feed 3/8 x 1 ¹/₄ bolts with washer on wire (supplied) through large chassis hole and out through holes in ECB steel mounting bracket. **FINGER TIGHTEN ONLY. See figure 5**.
- 9. Align steel mounting bracket level. **TIGHTEN ALL BOLTS** taking care not to over tighten front M6 bolts. **See figure 6**.
- 10. Remove original headlight / indicator assemblies from vehicle to access wiring. Three 10mm head bolts per assembly lift from guard side clip and pull forward off lower plastic clip. See figure 7. Splice ECB indicator / park light wiring into original wiring, use cable locks (supplied). Connect ECB indicators / park lights and check operation, once confirmed remove. Refit headlight / indicator assemblies to vehicle.
- 11. Splice ECB fog light wiring to vehicles original wiring harness, use cable locks supplied.



Tel: 07 3897 5700 Fax: 07 3283 1168 ecb@ecb.com.au_www.ecb.com.au

Po Box 122 Margate QLD 4019 Australia

- 12. Fit ECB LED indicator / park lights (supplied) into protection bar as per instructions supplied with the LED indicator kit. **NOTE: Ensure park light is to outside. See figure 8.**
- 13. Attach ECB fog lights to protection bar. Place M6 x 20 bolts, spring washers (supplied) through light mount from inside and attach nut to top. Slide assembly into light mount in Protection bar and centralize light to hole. **TIGHTEN FIRM ONLY. See figure 9.**
- 14. Fit 6mm clip lock trim (supplied) to rear of protection bar. Trim underside of each end to allow top of clip lock to cover to end of protection bar. See figures 10, 11 and 12.
- 15. Trim lower grille in bumper cover to fit around steel mounting brackets. See figure 13. NOTE: Trim out as minimal as possible. Refit bumper cover to vehicle. NOTE: As installing, reconnect temp sensor and feed indicator / park light wiring and fog light wiring out through bumper cover. Ensure wiring does is not trapped between mounting bracket and bumper and is sufficiently insulated against shorting. Do not reconnect original equipment bumper lights
- 16. Fit ECB protection bar to outside of steel mounting brackets. Use ½ x 1 ½ bolts, nuts and washers (supplied). **FINGER TIGHTEN ONLY.** Feed bolts from outside.
- 17. Align protection bar with vehicle. See figure 14 for front view and figure 15 for side view. TIGHTEN ALL BOLTS/NUTS. See figure 16.
- 18. Attach 6mm clip lock (supplied) to air vent cut outs in protection bar with flat side to front. Start at top centre feeding hard into all corners, overlap starting point by 3-4mm and cut off, force in. Ensure start and finish cuts are square. **See figure 17.**
- 19. Fit 3mm clip lock trim (supplied) to air vent cut outs in protection bar skirt. See figure 17.
- 20. Connect indicator / park light wiring and CHECK OPERATION.
- 21. Connect fog light wiring and **CHECK OPERATION.** Insert Fog light trims into Protection bar with large side to inside of protection bar.

ENSURE NUMBER PLATE IS CLEARLY VISABLE

Note: When fitting/refitting the licence plate to the vehicle, ensure there is no obstruction to licence plate vision in accordance with local authorities. If required relocate licence plate to an alternate location.

Further VFPS Notes:

- a) Do not attach VFPS to the vehicle using anchorages not intended for this purpose (e.g. engine mounting bolts).
- b) Do not use this product for any vehicle make or model, other than those specified by the VFPS manufacturer.
- c) Do not remove the plaque or label from the VFPS.
- d) Do not modify the structure of the VFPS in any way.
- e) No accessory or fitment should project forward of the VFPS forward profile.
- f) ENSURE THESE INSTRUCTIONS ARE LEFT WITH VEHICLE OWNER AND/OR OPERATOR.



Tel: 07 3897 5700 Fax: 07 3283 1168 ecb@ecb.com.au_www.ecb.com.au 29 Snook St Clontarf QLD 4019 Australia

Po Box 122 Margate QLD 4019 Australia

FITTING KIT

1 – Steel mounting bracket.	4 – M6 flat washers.
$4 - 3/8 \ge 1 \frac{1}{4}$ bolts, washers on 200mm wire	4 – M6 spring washers
4 - 3/8 nuts.	2 - M6 nuts
4 - 3/8 flat washers.	10 – Cable locks.
4 - 3/8 spring washers.	1 – ECB LED Indicator / Park light kit.
$4 - \frac{1}{2} \times \frac{1}{2}$ bolts	1 – Pair ECB Fog lights
$4 - \frac{1}{2}$ nuts	2 – Fog light trims
$8 - \frac{1}{2}$ flat washers.	1 – 2040mm length 6mm clip lock.
$4 - \frac{1}{2}$ spring washers.	2 - 600mm lengths 6mm clip lock.
4 – M6 x 20 bolts.	2 – 430mm lengths 3mm clip lock.



Figure 1



Figure 2



Figure 3 – Placing steel mounting bracket, ready for
installation, Turbo diesel vehicle.Figure 4© Copyright – ECB Pty Ltd – 2018



Figure 4 – Driver's side shown. Use 10mm longtrid = 2018drill bit as required.



Tel: 07 3897 5700 Fax: 07 3283 1168 ecb@ecb.com.au_www.ecb.com.au 29 Snook St Clontarf QLD 4019 Australia

Po Box 122 Margate QLD 4019 Australia



Figure 5 - Drivers side shown



Figure 7 – Drivers side shown Headlight assembly moved forward to access wiring






Figure 9




Figure 6 – Driver's side shown





Figure 8







Tel: 07 3897 5700 Fax: 07 3283 1168 ecb@ecb.com.au www.ecb.com.au 29 Snook St Clontarf QLD 4019 Australia

Po Box 122 Margate QLD 4019 Australia




Figure 11




Figure 12 – Passenger side shown



Figure 13



Figure 14 – Front view shown



Figure 16 Impact wrench access for nuts



Figure 15 – Side view shown



Tel: 07 3897 5700 Fax: 07 3283 1168 ecb@ecb.com.au_www.ecb.com.au 29 Snook St Clontarf QLD 4019 Australia

Po Box 122 Margate QLD 4019 Australia

6mm clip lock




Figure 17



Tel: 07 3897 5700 Fax: 07 3283 1168 ecb@ecb.com.au_www.ecb.com.au 29 Snook St Clontarf QLD 4019 Australia

Po Box 122 Margate QLD 4019 Australia

We value your comments

Dear Fitter,

ECB would like to know how you went with the installation of this product. We value your comment and may need to contact you to clarify some details so please complete your contact details clearly.

We would appreciate if you could complete as many of the following details as possible.

Your Name:	Your contact No.		
Product Part No.	Product Invoice No.	Product Invoice No.	
Product Description:	Make, model, and year of vehicle:		
Product Work Order No.	Company your from/	Company product purchased from:	
Date of Fitment://	Yes	No	
Was the fitting hardware supplied complete?			
If no what was not supplied			
	Yes	No	
Did the installation go well?			
Please provide comments			

Please draw diagrams if you need to.

Post to Reply Paid 122 PO Box 122 Margate QLD 4019 **Fax to** (07) 3283 1168



Tel: 07 3897 5700 Fax: 07 3283 1168 ecb@ecb.com.au_www.ecb.com.au 29 Snook St Clontarf QLD 4019 Australia

Po Box 122 Margate QLD 4019 Australia



Tel: 07 3897 5700 Fax: 07 3283 1168 ecb@ecb.com.au_www.ecb.com.au 29 Snook St Clontarf QLD 4019 Australia

Po Box 122 Margate QLD 4019 Australia

DESPATCH CHECKLIST BSZ58SY

ICZBKCSZ58

Work	Order #			
	Finish:			
Tr	ansport:			
D	ue Date:			
0	1 – Steel 1	nounting bracket.	See other side of	
0	1 – Bolt k	it.	this page for	
0	1 – ECB I	ED Indicator / Park light kit. B fog lights. ED Indicator / Park light kit.		
0	1 – Pair E			
0	2 – Fog li	ght trims.		
O 1 – 2040mm length 6mm clip lock.				
O 2 – 600mm lengths 6mm clip lock.				
O = 2 - 430mm lengths 3mm clip lock.				
<i>O</i> 2 – ECB Over riders – Fitted to Bar				
All parts	If NO	product "the best it can be" fix before continuing and <u>completed</u> by:	Yes/ Wrapper's initials / Checker initials	
Nut	and bolts:		Date_/_/	
Ord	ler control:		Date_/_/	
Final w	rap check:		Date_/_/	



Tel: 07 3897 5700 Fax: 07 3283 1168 ecb@ecb.com.au www.ecb.com.au 29 Snook St Clontarf QLD 4019 Australia

Po Box 122 Margate QLD 4019 Australia

